



Product data sheet

1 / 1

Product name **TUDAMELT 54/56**
Paraffin-pastilles

Customer product designation
Issue / Version 1 / 04/10/23

Typical product data

Analysis	Method	Unit	Typical
Congeaing Point	DIN ISO 2207	°C	55,0
Drop Point	Ph. Eur. 2.2.17	°C	56,0
Needle penetration 25 °C	DIN 51579	mm/10	18
Kin. Viscosity 100 °C	DIN EN ISO 3104	mm ² /s	3,800
Density 80 °C	DIN 51757 method 3	kg/m ³	770,0
Content of oil	DIN 51531	Mass.-%	0,5
Colour Saybolt	ASTM D6045	-	30

The above mentioned data are only an indication and do not represent any guarantee. Any deviations of the data are no reason for claim.



Certified according to:
DIN EN ISO 9001
DIN EN ISO 14001*
DIN EN ISO 45001*
DIN EN ISO 50001**
DIN EN ISO/IEC 17025**

Headquarters:
H&R Group
Am Sandtorkai 64
20457 Hamburg, Germany
Phone +49 40 43218-0
Fax +49 40 43218-400
Internet www.hur.com

Mineral oil and vaseline plant:
Tudapetrol Mineralölerzeugnisse
Nils Hansen GmbH & Co. KG*
Halskestraße 30-34
22113 Hamburg, Germany
Phone +49 40 781108-0
Fax +49 40 781108-199

Refinery Salzbergen:
H&R ChemPharm GmbH*, **
Neuenkirchener Straße 8
48499 Salzbergen, Germany
Phone +49 5976 945-0
Fax +49 5976 945-624

Refinery Hamburg:
H&R Ölwerke Schindler GmbH*, **
Neuhöfer Brückenstr. 127-152
21107 Hamburg, Germany
Phone +49 40 32523-0
Fax +49 40 32523-285